



# **ANTI-CORROSION FLUID**

# **ADDINOL KO 6 F SPRAY**

### **PRODUCT DESCRIPTION**

ADDINOL KO 6-F Spray is a solvent-containing multi-functional corrosion protective agent. Due to its composition it is water repellent and neutralizes hand perspiration. It displays good penetration properties, creeps under rust and has a lubricating effect.

## **APPLICATION**

Excellent suitability for temporary protection of metal surfaces:

- during in-house transportation and storage
- of spare parts and supply parts, semi-finished products
- of hand tools and do-it-yourself supplies
- in folds, gaps and spot-welding seams
- Simple application by spraying, dipping or brushing
- Fit for moist surfaces and, due to its excellent creeping effect, also suitable for loosening rusty friction connections (e.g. screw connections)

#### **DELIVERY**

Delivery in 500 ml aerosol cans (12 pieces/carton), drums and in small packages.

#### **PLEASE NOTE**

Compatibility with plastics must be checked for each individual case of application.

#### **CHARACTERISTICS**

- Water repellent
- · Neutralizes hand perspiration
- · Very good penetration properties
- · Creeps under rust
- Contains solvents
- Chlorine-, bromine- and fluorine-free propellant gas based on propane-butane

#### **ADVANTAGES AND BENEFITS**

- Usable for moist surfaces
- Does not leave fingerprints on workpieces
- · Quick spreading on workpieces
- Excellent corrosion prevention
- · Easy loosens tight connections
- After evaporation of the solvent, a thin, oily to slightly creamy protective film remains, which provides an excellent protection for storage under roof and in rooms
- · Ozone-friendly







# **ADDINOL KO 6 F SPRAY**

#### SPECIFICATIONS AND TYPICAL PARAMETERS

Feature	Test condition / unit		KO 6 F Spray	Method acc. to
Density – active agent	at 15°C	kg/m³	646	DIN 51757
Viscosity – active agent	at 40°C	mm²/s	5.5	DIN 51562-1
Flash point	coc	°C	< -20	DIN EN ISO 2592
Neutralization number		mg KOH/g	0.5	DIN 51588-1
Evaporation residue		%	2.5	
Test in a saturated atmosphere	min. 3 cycles		fulfilled	DIN 51386-1
Term of corrosion protection	open		> 3 days	DIN EN ISO 6270-2
	under roof		> 5 months	

## **ADDINOL - The Experts for High-Performance Lubricants**

We at ADDINOL develop and produce more than 600 high-performance lubricants of the new generation. Among these are automotive lubricants for highest demands and pioneering developments for industrial applications. Our customers all over the world benefit from the high and stable quality of our ADDINOL high-performance lubricants, our know-how and the individual customer advisory service of our competent experts. Our company has world wide activities. ADDINOL high-performance lubricants are distributed by more than 90 international partners.

The data given in this product sheet represent our current level of knowledge and experience. Due to the various specific application they do, however, not discharge the user from his own examination. The information provided herein may not be used to derive a legally binding warranty of specific properties or the suitability for a certain purpose of application. Detailed security-concerning and toxicological data as well as security instructions for each product can be taken from the corresponding Material Safety Data Sheets (MSDS). High-performance lubricants from ADDINOL are under continuous development. Therefore, ADDINOL Lube Oil GmbH keeps the right to change technical data in this product data sheet without notification. In case of doubt, please do not hesitate to contact our customers' advisory service.