



MASTERCHARGE 740



Overview

MASTERCHARGE 740

cod. 893002

Charging station for electric vehicles in AC alternating current (Mode 3).

Mastercharge is equipped with a built-in, 5-metre long charging cable with Type 2 connection and is suitable both for indoor and outdoor installations in protected zones (IP54, working temperature -20° C; +50° C).

Mastercharge can only be used via authentication with a RFID badge by authorised users only.







The charge status of the vehicle is always visible on the front led on the product.

Easy to install, Mastercharge is a plug-and-charge, safe and intuitive solution.

Features:

- 7,4 kW power (32A 230V singlephase);
- Mode 3 connection, Type 2 connector;
- 5-metre long cable;
- Activation via RFID badge (4 cards supplied);
- Rating IP54;
- Complies with LVD (EN 61851-1, EN 61851-22) and EMC (EN 61000-6-2, EN 61000-6-3) norms.

Technical data

CODE	CODE 893002		STAND-BY POWER 3		OVERVOLTAGE CATEGORY III
V_{1PH}	SINGLE PHASE MAINS VOLTAGE 230 V		EV CONNECTOR TYPE Type 2		DIMENSIONS 32,5 x 21, 5 x 7,7 cm
F	MAINS FREQUENCY 50 Hz	MODE	RECHARGE MODE Mode 3		WEIGHT 4,5 kg
P_{MAX}	MAX ABSORBED POWER 7,4 KW		CABLE TYPE Case C	BAR CODE	EAN CODE 8056151818423
A_{MAX}	MAX CURRENT 32 A	IP	PROTECTION DEGREE IP54		