



A safety shoe with many features. Perfect for those who work in moist environments.

**jalas® EXALTER 9965**

EN ISO 20345:2011 S3, SRC, HRO ASTM F2413-18 M/I/C SD 35 PR



Learn more

**LOW-CUT, WATER REPELLANT WITH BOA®**

This low-cut safety shoe has the features you need for most work situations, such as PTC-textile nail protection, toecap in aluminum and high-grip Vibram Nitrile rubber outsole. The multilayer insole together with the sock-like construction provide ultimate comfort. PORON® XRD™ shock-absorption prevents injuries to foot and back. The upper is water repellent, perfect for those who work in moist environments. BOA® Fit System makes it easy to put on and take off the shoe.

**CHARACTERISTICS**

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

**FUNCTIONS**

- Double shock absorption zones
- Water repellent
- Specially designed details
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Polstered shaft edge
- Ventilating insole
- Ergonomically shaped
- Conforms with IEC 61340-5-1 (ESD)
- Quick-tie
- Stabilizator
- BOA® Fit System
- Soft
- Free from animal-derived materials



**PREVENTS RISK OF**

Toe injuries, nail penetration, sprain injuries, antistatic

**PRIMARY ENVIRONMENTS OF USE**

Outdoors, indoors, environments with risk for outsole penetration, clean environments

**SPECIFICATION**

TYPE Safety footwear, Low shoes

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

COLLECTION Exalter

UPPER MATERIAL Microfiber, Textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

INSOLE FX3 Supreme

INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Polyester-based conductive thread, Neo foam, Poron® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING BOA® Fit System

COLOUR Black, Red

NET WEIGHT, (SIZE 42) 1,28 kg

**COMPLIANCE**



TP TC 019:2011

EN ISO 20345:2011  
S3, SRC, HRO


ASTM F2413-18  
M/I/C  
SD 35 PR




ÖNORM Z 1259



**FEATURES**



Anti-static properties



Ergothan Shock Absorption System




ESD




Aluminium toecap




Oil-resistant outsole



Heat-resistant outsole



Water repellent



Nail protection in plasma-treated composite (PTC) textile



Stabilizator

| SIZE |      |      |      | ARTICLE NUMBER | EAN          |
|------|------|------|------|----------------|--------------|
| EU   | UK   | US M | US W |                |              |
| 34   | 1.5  | 2.5  | 3.5  | 9965-34        | 198106004142 |
| 35   | 2    | 3.5  | 4    | 9965-35        | 198106004135 |
| 36   | 3    | 4    | 5    | 9965-36        | 198106004128 |
| 37   | 4    | 5    | 6    | 9965-37        | 198106004111 |
| 38   | 5    | 5.5  | 6.5  | 9965-38        | 198106004104 |
| 39   | 6    | 6.5  | 7.5  | 9965-39        | 198106004098 |
| 40   | 6.5  | 7.5  | 8.5  | 9965-40        | 198106004081 |
| 41   | 7    | 8    | 9    | 9965-41        | 198106004074 |
| 42   | 8    | 9    | 10   | 9965-42        | 198106004067 |
| 43   | 9    | 9.5  | 11   | 9965-43        | 198106004050 |
| 44   | 10   | 10.5 | 11.5 | 9965-44        | 198106004043 |
| 45   | 10.5 | 11   | 12.5 | 9965-45        | 198106004036 |
| 46   | 11   | 12   | 13   | 9965-46        | 198106004029 |
| 47   | 12   | 13   | 14   | 9965-47        | 198106004012 |

**ejendals**

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com