

Provides ankle support, extended impact protection and keep the feet dry.



■*jalas*® Exalter 9985

EN ISO 20345:2011 S3, SRC, HRO ASTM F2413-18 M/I/C SD 35 PR ASTM F3445-21 SR

MID-CUT, WATER REPELLANT WITH BOA

This mid-cut safety shoe has the features you need for most work situations, such as PTC-textile nail protection, toecap in aluminum and high-grip Vibram Nitrile rubber outsole. The model provides extra ankle support and PORON[®] XRD[™] shock-absorption prevents injuries to foot and back. The upper is water repellant, perfect for those who work in moist environments. BOA° Fit System makes it easy to put on and take off the shoe.

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- Water repellent
- Specially designed details
- Double shock absorption zones
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Polstered shaft edge
- Ventilating insole •
 - Conforms with IEC 61340-5-1 (ESD)
- Quick-tie
- Stabilizator
- BOA[®] Fit System
- Ergonomically shaped

- Soft
- Ankle support
- Free from animal-derived materials

lioreli

2024-03-06



ď





■jalas® EXALTER 9985

PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration, clean environments

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots CATEGORY Cat. II NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile FITTING Regular **COLLECTION** Exalter UPPER MATERIAL Microfiber, Textile TOECAP MATERIAL Aluminium LINING MATERIAL Polyester **INSOLE** FX3 Supreme INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Polyester-based conductive thread, Neo foam, Poron[®] XRD[®] MIDSOLE MATERIAL PU midsole OUTSOLE MATERIAL Nitrile rubber outsole FASTENING BOA Fit System COLOUR Black, Red NET WEIGHT, (SIZE 42) 1,34 kg

COMPLIANCE



S3, SRC, HRO

2011 ASTM M/I/C

ASTM F2413-18 M/I/C



SD 35 PR

CGUV 112-191

FAL

FEATURES



50

Aluminium toecap



Nail protection in plasma-treated composite (PTC) textile

Ergothan Shock

Absorption System

Oil-resistant outsole

Heat-resistant outsole

TP TC 019:2011

ASTM F3445-21

ESD

SR

SIZE				ARTICLE	EAN
EU	UK	US M	US W	NUMBER	LAN
34	1.5	2.5	3.5	9985-34	198106003725
35	2	3.5	4	9985-35	198106003718
36	3	4	5	9985-36	198106003701
37	4	5	6	9985-37	198106003695
38	5	5.5	6.5	9985-38	198106003688
39	6	6.5	7.5	9985-39	198106003671
40	6.5	7.5	8.5	9985-40	198106003664
41	7	8	9	9985-41	198106003657
42	8	9	10	9985-42	198106003640
43	9	9.5	11	9985-43	198106003633
44	10	10.5	11.5	9985-44	198106003626
45	10.5	11	12.5	9985-45	198106003619
46	11	12	13	9985-46	198106003602
47	12	13	14	9985-47	198106003596

ejendals Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com