

## **BOLT™ 200 White Vented**

## **BOLT™ 200**

- Shell made of Lexan<sup>™</sup> ultra resistant to impacts.
- BOLT<sup>™</sup> system ensure compatibility among a large range of accessories with an easy and intuitive attachment system.
- Extremely comfortable and easy to adjust wheel ratchet adjustment system.
- Foam suspension provides consistent impact performance independent of impact location.
- Comfortable inner foam suspension paired with a crown liner for extra comfort.
- Breathable, washable and replaceable premium sweatband.
- Breathable, washable and replaceable premium crown liner.
- Vented version delivered with a mounted EN 12492 certified chinstrap (colour coded red).
- Unvented version delivered with a mounted EN 397 certified chinstrap (colour coded grey).
- Certified as per EN 397:2012 with optional requirement for Extreme temperatures – 40°C (vented and unvented version), Lateral Deformation (vented and unvented version) and Electrical insulation 440 V a.c. (unvented version).
- Vented version certified as per EN 12492:2012. Unvented version provides protection in conformity of EN12492: 2012 except clause 4.1.4.
- Size: 52 68 cm.
- 8 colours available with matte finish: white, yellow, orange, red, black, green, blue and high visibility yellow.
- Unvented version certified EN 50365 Electrically insulating helmets for use on low voltage installations.





Vented	Unvented
Description	Article Number
Description	Article Number
BOLT™200 White Vented - 1pc	4932478141
BOLT™200 White Unvented - 1pc	4932479252
BOLT™200 Yellow Vented - 1pc	4932478918
BOLT™200 Yellow Unvented - 1pc	4932479253
BOLT™200 Red Vented - 1pc	4932478919