HAPAX FIXING PRO HIDDEN FASTENING SYSTEM











CHARACTERISTICS

- Totally invisible.
- Rot-proof.
- Weather resistant and pulling endurance of 650kg.
- Very strong hold.
- Adjustable.
- Excellent ventilation.
- Complete with stainless steel screws AISI 410.
- Universal: for boards with 90 to 200 mm width and 19 to 40 mm height.
- Material: fibreglass reinforced composit.
- Freeze resistant: -40°C.
- Heath resistant: 110°C.
- Maximal spacing: 50 cm.
- Possible to change 1 board without damaging the rest.

ADVANTAGES

- Fast.
- UV resistant and resistant to extreme temperatures.
- 100 % recyclable.
- Can be used with any type of joist but also (if required) directly on the tile or concrete (when the available height does not allow the use of a joist).
- Assures an excellent ventilation between the boards and the joists: the use of bituminous strips is not longer necessary.
- 100% invisible: No metal parts or screws are visible. The spacings between the boards are regular. Esthetical and professional result. Moreover, the Hapax Fixing Pro system does not require special parts for the first and last board.
- Easy and quick installation: installed with two stainless steel screws under the boards.
- No profile is necessary.
- Meets the requirements of DTU 51.4.



USABLE WITH

Can be used with the following types of wood: Ipê, African Padauk, bamboo, ash, poplar and oak, accoya, kiln dried cumaru, kiln dried tali, kiln dried Afrormosia, Afzélia, kiln dried Bankirai, kiln dried Iroko, Merbau, Moabi, Sapelli, Sipo, kiln dried Tatajuba, Teak, Canadian Western Red Cedar.



Front view 35 mm Side view





Manual





d x l [mm]	d x w x l [mm]	Art. Nr.	EAN code		
5,5 x 30 5,5 x 35	35 x 13 x 180	HAP010C00FIXPRO3	5410439473682	100 x Fixing 200 x 5,5 x 30 mm 100 x 5,5 x 35 mm	88 boxes
5,5 x 30 5,5 x 35	35 x 13 x 180	HAP010B00FIXPRO3	5410439475983	100 x Fixing 200 x 5,5 x 30 mm 100 x 5,5 x 35 mm	88 boxes
5,5 x 35	35 x 13 x 180	HAP011C00FIXPRO3	5410439473699	100 x Fixing 300 x 5,5 x 35 mm	88 boxes