



# Spirit Level Aluminium PV

Extra strong aluminium profile measuring 59x26 mm and weighing 880 g/m. Transparent and durable Crush-proof block vials with temperature-proof vial mountings, highly resistant to ultraviolet light and temperature fluctuations. Horizontal vial with a +30% magnification lens and luminescent reflector.

## Features

- Tolerance in normal position is  $\pm 0.5$  mm/m, upside down  $\pm 0.5$  mm/m.
- Focus vial with colour markings for easy reading and with a 200 mm radius giving a sensitivity of 10 mm/m.
- Shock absorbing end protectors with anti-slip function.
- The liquid in the vial is a low viscosity coloured oil mixture that gives the bubble optimal freedom of movement.
- The anti-static properties of the liquid means that the bubble is not affected by static electricity.



30 % magnification, UV-safe, Vial glows in dark, Sensitivity 10.0 mm/m, Tolerance +/-0.5 mm/m reversed, Tolerance +/-0.5 mm/m standard

PRODUCT	STOCK CODE
SPIRIT-LEVEL PV 40	414001
SPIRIT-LEVEL PV 60	414101
SPIRIT-LEVEL PV 80	414201
SPIRIT-LEVEL PV 100	414301
SPIRIT-LEVEL PV 120	414401
SPIRIT-LEVEL PV 140	414501
SPIRIT-LEVEL PV 200	414701